

 [Print](#) | [Close Window](#)

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1400 Case



1400 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

1400 Case Configurations

Cat. #	Description
1400	1400 Case
1400NF	1400 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1400 Case Specifications

Exterior Dimensions (L x W x D)

13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)

Lid Depth

1.18" (3 cm)

Weight w/Foam

4.41 lbs. (2 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

Interior Dimensions (L x W x D)

11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)

Bottom Depth

4.00" (10.2 cm)

Total Depth

5.18" (13.2 cm)

Weight w/o Foam

3.97 lbs. (1.8 kg)

Buoyancy Max.

20.06 lbs. (9.1 kg)

Personalized Nameplate Available

1400 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1400 Case Accessories

Cat. #	Description
1400IP	Instapak Quick® RT
1400PF	Special Application Panel Frame
1401	3 pc. Replacement Foam Set
1403	Replacement O-ring

Pelican™ Products, Inc. Canada
 10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
 Click to contact us • www.pelican.ca