

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1660 Case



1660 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Large 2-person fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

1660 Case Configurations

Cat. #	Description
1660	1660 Case
1660NF	1660 Case (No foam)
1664	1660 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request

1660 Case Specifications

Exterior Dimensions (L x W x D)

31.50" x 22.87" x 19.00" (80 x 58.1 x 48.2 cm)

Interior Dimensions (L x W x D)

28.18" x 19.75" x 17.62" (71.5 x 50.1 x 44.7 cm)

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth

3.50" (8.9 cm)

Bottom Depth

14.12" (35.9 cm)

Total Depth

17.62" (44.7 cm)

Weight w/Foam

42.11 lbs. (19.1 kg)

Weight w/o Foam

34.17 lbs. (15.5 kg)

Buoyancy Max.

350.1 lbs. (158.8 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

No. of Wheels

4

Personalized Nameplate Available

1660 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1660 Case Accessories

Cat. #	Description
1661	5 pc. Replacement Foam Set
1662	Pick 'N' Pluck™ Sections Only (set of 3)
1663	Replacement O-ring
1665	Padded Divider Set Only
1669	Photo/Lid Organizer for 1660 Case

Pelican™ Products, Inc. Canada
 10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
 Click to contact us • www.pelican.ca